



30 GALLON 3-NOZZLE 3 POINT SPRAYER



HIGHFLO
HIGH PERFORMANCE

BEST IN CLASS PUMP

- 2.4 GPM High Performance 12 Volt Pump
- Maximum Pressure Of 60 PSI
- Pressure Switch Turns Pump On & Off
- Self Priming - Can Run Dry Without Damage
- Fuse Protected
- Chemical Resistant Components
- Fan Cooled To Promote Longevity & Efficiency



FUSE PROTECTED 8 FT LEAD WIRE

- Helps Protect Your Vehicle Wiring
- Alligator Clips & On/Off Switch Included



MANIFOLD W/PRESSURE GAUGE

- Lever Ball Valves Allow Flow & Pressure Control
- Easily Monitor Pressure With Highly Visible Gauge
- Quick Connect Fittings Enables Fast Configuration



5 INCH TANK LID

- Lid Tethered To Tank
- Splash Prevention Flap In Lid
- Venting Reduces Tank Pressure



IN TANK / INLINE STRAINER

- 3/8 Inch Hose Barb Connection
- Minimizes Chemical Waste



LEVER GRIP SPRAY WAND

- Up To 30 Feet Horizontal Spray
- Up To 16 Feet Vertical Spray
- Adjustable Spray Pattern



15 FEET OF 3/8 INCH HOSE

- Chemical Resistant Rubber Hose
- Remains Flexible
- Less Prone To Kinking



PREMIUM SPRAY TIPS

- TeeJet AI XR11002 Air Induction XR Flat Spray Tips
- Reduces Chemical Drift
- Includes Check Valve Strainer



3-NOZZLE FOLDING STEEL BOOM

- Delivers 7.5 Feet of Spray Coverage
- 30 Inch Nozzle Spacing
- 62" Folding Steel Boom



3 POINT HITCH

- Category 1
- Steel Construction

30-3N-3PT-GS
5303678