

65 GALLON 3-NOZZLE BROADCAST 3 POINT SPRAYER





6 ROLLER PUMP

- Hypro 6 Roller Pump
- 9.76 GPM at 540 RPM
- 8.2 GPM at 1000 RPM
- Max Pressure 300 PSI
- Max Speed 1200 RPM
- Max Output 21.8 GPM



DIE CAST QUICK COUPLER

- Multi-Speed Die Cast Quick Coupler
- Easy PTO Connection



DIRECT-O-VALVE MANIFOLD

- Constructed from Corrosion Resistant Materials
- Piston Type Pressure Relief / Regulating Valve
- Easily Monitor Pressure With Highly Visible Gauge



5 INCH TANK LID

- Lid Tethered To Tank
- Splash Prevention Flap In Lid
- Venting Reduces Tank Pressure



DELUXE PISTOL GRIP SPRAY WAND

- Up To 45 Feet Horizontal Spray
- Up To 30 Feet Vertical Spray
- Adjustable Spray Pattern



25 FEET OF 3/8 INCH HOSE

- Chemical Resistant Rubber Hose
- Easy To Wrap For Storage
- Less Prone To Kinking



PREMIUM SPRAY TIPS

- Exclusive Nozzle Bodies And Spray Tips
- Includes On/Off Valves & Drip Free Nozzles
- Each Nozzle Can Be Used Independently



3-NOZZLE BROADCAST BOOM

- Broadcast Boom Delivers 36 Feet Of Spray Coverage
- End Nozzles Sprays 15 Feet
- Center Nozzle Sprays 6 Feet



3 POINT CARRIER FRAME

- Provides Strength And Support To The Tank
- Connects To The 3-Point Hitch On A Tractor
- Supports The Tank And Boom

3PT-65-6R-BL 5303235