



65 GALLON BOOMLESS 3 POINT SPRAYER



DIRECT-O-VALVE MANIFOLD

- Constructed from Corrosion Resistant Materials
- Piston Type Pressure Relief / Regulating Valve
- Easily Monitor Pressure With Highly Visible Gauge



PREMIUM SPRAY TIPS

- Exclusive Nozzle Bodies And Spray Tips
- Includes On/Off Valves & Drip Free Nozzles
- Each Nozzle Can Be Used Independently



5 INCH TANK LID

- Lid Tethered To Tank
- Splash Prevention Flap In Lid
- Venting Reduces Tank Pressure



25 FEET OF 3/8 INCH HOSE

- Chemical Resistant Rubber Hose
- Easy To Wrap For Storage
- Less Prone To Kinking



DELUXE PISTOL GRIP SPRAY WAND

- Up To 45 Feet Horizontal Spray
- Up To 30 Feet Vertical Spray
- Adjustable Spray Pattern



3-NOZZLE BROADCAST BOOM

- Broadcast Boom Delivers 36 Feet Of Spray Coverage
- End Nozzles Sprays 15 Feet
- Center Nozzle Sprays 6 Feet



3 POINT CARRIER FRAME

- Provides Strength And Support To The Tank
- Connects To The 3-Point Hitch On A Tractor
- Supports The Tank And Boom

**DOES NOT INCLUDE PUMP OR COUPLER
REQUIRES ROLLER PUMP ASSEMBLY**

3PT-65-NR-BL
5303255